



# HERMITAGE


## TECHNICAL SPECIFICATIONS




WIDTH OF THE WALLCOVERING 110CM (44")  
LARGEUR DU MURAL 110CM (44")  
BREITE DER WANDBEKLEIDUNG 110CM (44")  
BREEDETE 110CM (44")




ANTI-DUST AND ANTI-MOISTURE TREATMENT  
TRAITEMENT ANTI-TACHE  
SCHMUTZABWEISEND  
VLEKBESTENDIG




SOLD BY CUT LENGTH  
VENDU AU METRE LINEAIRE  
METERWARE  
LEVERBAAR PER METER




GOOD LIGHT RESISTANCE  
SOLIDE A LA LUMIERE  
GUT LICHTBESTANDIG WERT  
GOEDE LICHTECHTHEID



PLACE JOIN TO JOIN  
PLACER JOINT CONTRE JOINT  
GERADER ANSATZ  
STOTEND PLAATSEN



NO RAPPORT  
PAS DE RACCORD  
ANSATZFREI  
GEEN RAPPORT



DO NOT REVERSE ALTERNATE PIECES  
NE PAS INVERSER LES LEZ  
NICHT GESTURZT  
NIET STORTEN



WALLCOVERING ON NON WOVEN BACKING  
TEXTILE SUR NON-TISSE  
VLIESTRAGER  
TEXTIEL OP NON-WOVEN DRAGER




ECOLOGICAL  
ECOLOGIQUE  
OKOLOGISCH  
ECOLOGISCH



SPLIT  
STRIPABLE  
SPALTBAR - TROCKEN ABZIEHBAR  
SPLITBAAR



FIRE RESISTANT  
CLASSEMENT AU FEU  
FEUERBESTANDIG  
BRANDNORM



APPLY A READY MIXED PVA OR EVA CLEAR ADHESIVE DIRECTLY TO THE WALL / NO NEED TO HUMIDIFY THE BACK OF THE WALLCOVERING  
ENCOLLER LE MUR AVEC UNE COLLE EN PATE VINYLIQUE PRETE A L'EMPLOI / NE PAS HUMIDIFIER LE DOS DU REVETEMENT  
WAND EINKLEISTERN MIT EINEM FERTIGEN DISPERSIONSKLEBER TAPETEN / RUCKSEITE NICHT ANFEUCHTEN  
MUUR INLIJMEN MET PVA LIJM / BEHANG NIET BEVOCHTIGEN